



# Z200

Heating > Heatpump > Z200

- + The most compact
- + Guaranteed heating thanks to heating priority
- + Suits most pools






**3 YEAR**  
WARRANTY

**5 YEAR**  
CONDENSER  
WARRANTY  
ANTI-CORROSION

Product offered for sale on the «pool dealer» channel

	Z200 M2	Z200 M3	Z200 M4	Z200 M5
<b>PRODUCT REFERENCE</b>				
Standard model	WH000010	WH000011	WH000012	WH000013

<b>ACCESSORIES INCLUDED IN THE PACK</b>		
		
Winter cover	PVC fittings 1/2 unions 40 & 50	Anti-vibrations pads

<b>EQUIPMENTS</b>	
<ul style="list-style-type: none"> <li>• Horizontal blowing</li> <li>• Polypropylene body</li> <li>• Digital display</li> <li>• Heating priority mode (filtration pump control)</li> <li>• Automatic defrosting (forced ventilation)</li> <li>• Anti-freeze thermostat (minimum operating temperature: +5°C)</li> <li>• HP &amp; LP safety pressure switch</li> </ul>	<ul style="list-style-type: none"> <li>• Water flow switch</li> <li>• Titanium water exchanger condenser</li> <li>• Rotary vane compressor</li> <li>• Capillary expansion valve</li> <li>• Refrigerant fluid: R410A</li> </ul>

<b>PERFORMANCE: AIR 28°C / WATER 28°C / HUMID. 80%</b>				
Operating power (kW)	6.1	9	12	14.1
Consumed power (kW)	1.1	1.9	2.5	3
COP	5.6	4.7	4.8	4.7
<b>PERFORMANCE: AIR 15°C / WATER 26°C / HUMID. 70%</b>				
Operating power (kW)	4.6	6.3	8.4	10.2
Consumed power (kW)	1	1.6	2.1	2.6
COP	4.5		4.0	

TECHNICAL SPECIFICATIONS				
Recommended pool volume* (m³)	0-30	20-45	30-60	40-70
Average water flow (m³/h)	3	4	5	
Hydraulic connection	PVC 1/2union, Ø 40 or 50, glued			
Electric power supply	230 V / 1 / 50 Hz			
Nominal operating power (A)	4.45	7.09	9.36	11.2
Maximum operating power (A)	5.2	8.7	12.4	15.7
Power cable size	3 x 2,5			
Refrigerant fluid quantity (g)	0.73	0.95	1.06	1.1
Acoustic pressure at 10m (dB(A))	38.2	39.1	40.6	43.7

\*Estimated average values for a private pool with isothermal cover, from 15 May to 15 September.

\*\*For a maximum length of 20 meters.